


**ELECTRICAL SPECIFICATIONS**

Frequency Range: 3-6 GHz  
 Impedance: 50 Ohm  
 Insertion Loss: 0.60 dB max.  
 Isolation: 18 dB min.  
 VSWR: 1.40 max.  
 Forward Power: 100W  
 Direction: Clockwise

Revisions			
Rev	Description	Date	Approved:
A	Initial Release	2015.6.27	A. M



NOTES:  
 1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME  
 2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

Drawn:	W. Y 2015.6.27
Checked:	T. L 2015.6.27
Approved:	A. M 2015.6.27
Unless Otherwise Specified Dimensions are in Millimeters, Dimensions in [ ] are in Inches for Customer Reference Only. Unless Otherwise Specified Tolerance are: .XX ±0.13 [.005"] .X ±0.20 [.008"] X ±0.50 [.019"] .X° ±1° X° ±2°	

Title:	SMA Circulator Freq 3-6 GHz
Part No:	DCC300600B



View:	
Size:	A3
Scale:	2:1
Sheet:	1/1
Rev:	A