


ELECTRICAL SPECIFICATIONS

Frequency Range: 2-8 GHz
 Impedance: 50 Ohm
 Insertion Loss: 1.5 dB max.
 Isolation: 12 dB min.
 VSWR: 1.80 max.
 Forward Power: 20 W
 Reserve Power: 10 W


Revisions			
Rev	Description	Date	Approved:
A	Initial Release	2016.7.19	A. M




NOTES:
 1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
 2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

Drawn:	W. Y 2016.7.19
Checked:	T. L 2016.7.19
Approved:	A. M 2016.7.19
Unless Otherwise Specified Dimensions are in Millimeters, Dimensions in [] are in Inches for Customer Reference Only. Unless Otherwise Specified Tolerance are: .XX ±0.13 [.005"] .X ±0.20 [.008"] X ±0.50 [.019"] .X° ±1° X° ±2°	

Title:	SMA Isolator Freq 2-8 GHz
Part No:	DCI200800B


www.deewave.com

View: 

Size:	Scale:	Sheet:	Rev:
A3	1.5:1	1/1	A