


**ELECTRICAL SPECIFICATIONS**

Frequency Range: 1-2 GHz  
 Impedance: 50 Ohm  
 Insertion Loss: 1.4 dB max.  
 Isolation: 32 dB min.  
 VSWR: 1.40 max.  
 Forward Power: 100 W  
 Direction: Clockwise

Revisions			
Rev	Description	Date	Approved:
A	Initial Release	2015.11.13	A. M



- NOTES:
1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
  2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

Drawn:	W. Y 2015.11.13
Checked:	T. L 2015.11.13
Approved:	A. M 2015.11.13
Unless Otherwise Specified Dimensions are in Millimeters, Dimensions in [ ] are in Inches for Customer Reference Only. Unless Otherwise Specified Tolerance are: .XX ±0.13 [.005"] .X ±0.20 [.008"] X ±0.50 [.019"] .X° ±1° X° ±2°	

Title:	Dual-Junction Circulator, SMA Female, Freq 1-2 GHz
Part No:	DDCC100200B

**DEEWAVE**  
[www.deewave.com](http://www.deewave.com)

View:

Size: A3	Scale: 1:1	Sheet: 1/1	Rev: A
----------	------------	------------	--------